



GOA@60



Government of Goa
 DIRECTORATE OF SKILL DEVELOPMENT & ENTREPRENEURSHIP
FARMAGUDI GOVERNMENT INDUSTRIAL TRAINING INSTITUTE
 Farmagudi-Ponda-Goa, 403401
 Ph: (0832) 2980070

Website: www.itifarmagudi.goa.gov.in

Email: farmagudi-iti.goa@nic.in

Ref.No : 148/FGD/ITI/STR/Renovation of Ladies Trainees Toilet(DM)/STRIVE/2022/425 Dated: 27/05/2022

To,

Sub :- Inquiry of Renovation of Ladies Trainees Toilet Reg...

Sir,


Quotations are invited in sealed envelopes as per the specification and quantity mentioned below:-

Sr. No	Items/ Specifications	Qty	Unit Nos/Kg	Rate per unit Rs.	Taxes	Amount Rs.
	ANNEXURE					
Total amount						
Taxes						
Grand Total						

The terms and conditions for Supply shall be as under:-

- The Construction should be carried out at Farmagudi Government I. T. I. within 15 days of placing work order at Farmagudi Industrial Training Institut Farmagudi, Ponda- Goa.
- GST and any other levy applicable at the time of quotation may be shown separately in the quotations; otherwise it will be presumed that the prices offered are inclusive of all taxes.
- The rate quoted shall be inclusive of packing & forwarding charges freight paid for destination Farmagudi Industrial Training Institute, Farmagudi, Ponda- Goa.
- The quotations shall be valid for 45 days from the date of the opening of the same.
- The quotation will be evaluated for Renovation of Ladies Trainees Toilet together. Therefore, the rates for renovation charges including material may be quoted together.
- The materials if not accepted after inspection shall be collected by the supplier immediately with written assurance to supply the same as per the specifications as mentioned in the work order. The Farmagudi Industrial Training Institute, Farmagudi, Ponda- Goa, shall not be responsible for security/ storing.
- This office reserves the right to accept or reject any quotations without assigning any reason thereof.
- The warranty/guarantee shall be furnished with the item as the case may be.
- The extension of limit will be granted at the discretion of I.T.I. on genuine grounds by the written request of the supplier.
- The quotation should reach to this office on or before **08/07/2022** at 2:30 p.m either by return e-mail, hand delivery or by post and will be opened on same day i.e. on **08/07/2022** at 3:30 p.m.

Yours faithfully,



(S. S. Gaonkar)

Principal(Sr Scale)/Member Secretary

Copy to 1) The Account Section, Farmagudi, Govt.I.T.I., Farmagudi, Ponda- Goa
 2)O/c

ANNEXURE :- RENOVATION OF LADIES TRAINESS TOILET.

Sr. No	GSR Ref.	Description	Unit	Qty	Rate	Amount.
1	12053	Dismantling the tile work in floors and roofs laid in cement including stacking of materials within 50 meters lead for thickness of tiles 10mm to 25mm.	Sq.m.	47.03		
2	12042	Dismantling doors ,windows and clearestory windows (steel or wood) shutters including chowkhats architrave holdfast etc. complete and staking within 50 mt. Lend a) Of area 3sq.m. and below.	each	4.00		
3	11070	Removing dry or oil bound distemper by scrapping sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete.	Sq.m.	52.39		
4	7037	Providing and fixing louvers 50 mm wide in grooves in clerestory window frames excluding the cost of frames.				
	b)	Glass sheets 3 mm thick	Sq.m.	1.70		
5	15740	Providing and fixing NICKEL chrome plated copper alloy Fancy long body bib cock with wall flange Jaquar make or equivalent. Confirming to IS 8931;1993				
	a)	15mm nominal bore	each	5.00		
6	RA	Providing and fixing NICKEL Chrome plated Angular stopcock with wall flange of Jaquar make or equivalent etc.complete.	each	2.00		
7	15716	Providing and fixing nahani trap of rigid PVC(approved make) for S.W.R. pipes including lubricating etc complete, without door:				
	a)	110 mm dia	each	2.00		
8	15634	Providing & fixing c.p. brass towel rail complete with C.P. brass brackets fixed to wooden cleats with C. P. brass screws				
	b)	600 x 20 mm size	each	2.00		
9	15632	Providing and fixing 600 x 450 mm bevelled edge mirror of superior glass (of approved quality) complete with 6 mm thick asbestos sheet ground fixed to wooden cleats with C. P. brass screws and washers.	each	2.00		




Sr. No	GSR Ref.	Description	Unit	Qty	Rate	Amount.
10	12001	Repairs to plaster in patches of 2.5 sq.m. and under including cutting the patch in proper shape and preparing and plastering the surface of the walls complete including disposal of rubbish to the dumping ground within 50m lead				
		With cement mortar 1:4 (1 cement: 4 fine sand)	Sq.m.	21.80		
11	9076	Providing and laying antiskid floor tiles 12 x 12 upto 16 x 16 in of Johnson, Somany, Kajaria (thickness to be specified by the manufacturer) of 1st quality conforming to IS:15622 of approved make in shades as specified laid on 20 mm thick cement mortar 1:4 (1 Cement: 4 Coarse sand) including pointing the joints with white cement and matching pigment etc., complete				
	a)	Dark Shades	Sq.m.	12.25		
12	9073	Providing and fixing coloured ceramic tiles (Bell or equivalent) of 16" x 16" size and 6 mm thick in skirting and dados on 12 mm thick cement plaster 1:3 (1 cement: 3 coarse sand) and jointed with cement slurry complete.	Sq.m.	34.78		
13	7162	FRP (Fiber Reinforced Polymer) Frames Manufacture, Supply and Installation (with anchor fastener) of EPEE or equivalent Goan make FRP (Fiber Reinforced Polymer) Frame of cross section as per options below with right angle joint and FRP (Fiber Reinforced Polymer) laminate made from 450 grams per sq.mts (gam) chop strand glass fiber (matt) and unsaturated polyester resin with viscosity range of 400/450 centipoises per second (cps). The core of frame would be filled with seasoned wood as infill material. The slot of frame for door resting will be of suitable width so as to take specified thickness door.. The frame will be water proof as well as mild acid/alkali resistant manufactured in an ISO 9001-2015 certified company.				
		Specified Cross Section b) 4" x 2"	meter	10.20		



Sr. No	GSR Ref.	Description	Unit	Qty	Rate	Amount.
14	7160	<p>Standard Wood Core Door Shutter with Single Colour Manufacture, Supply and Installation (including accessories as mentioned below) of EPEE or equivalent Goan make FRP (Fiber Reinforced Polymer) door shutter of specified thickness as per options below by using tray system with seasoned hard wood, moisture less than 17%, wood styles for Top rail and lock rails.</p> <p>FRP (Fiber Reinforced Polymer) laminate made up of 450 grams per sq.mts (gsm) chop strand matt and unsaturated polyester resin with viscosity range of 400/450 centipoises per second (cps).The core of Shutter will be filled with MR2nd grade Block Board. The shutter to be water proof as well as mild acid/ alkali resistant manufactured using RV TIFAC</p>				
		<p>(RV Engineering College, Bangalore & Technology Information Forecasting & Assessment Council) technology in line with IS 13034 1990 test Standard in an ISO 9001 2015 certified factory.</p> <p>Accessories: i) S. S. Hinges 4"-3 Nos ii) S. S. Latch - 1 No iii) Tower Bolt 5" -2 Nos iv) Handle 5" =2 Nos</p>				
		Shutter Thickness: a) 32mm	Sq.m.	3.01		
15	11083	Painting two or more coats (excluding priming coat) with superior quality ready mixed paint for wood work of approved brand & manufacture in all shades on new work to give an even shade.	Sq.m.	3.44		
16	11081	Painting two or more coats (excluding priming coat) with superior quality ready mixed paint for steel work of approved brand & manufacture in all shades on new work to give an even shade.	Sq.m.	1.70		

Sr. No	GSR Ref.	Description	Unit	Qty	Rate	Amount.
17	11062	Distemping two or more coats, with oil bound washable distemper of approved brand and manufacture and of required shade on new work over and including a priming coat with distemper primer of approved brand and manufacture to give an even shade.	Sq.m.	52.39		


(S. S. Gaonkar)
Principal (Sr. Scale)
Farmagudi Govt. I. T. I.